












磁力鎖與支架

- ▶ 安全、防盜、堅固、耐用、提供雙色LED 狀態指示燈。
- ▶ 產品規格從最小磅數90磅至最大磅數1500磅、可供選則同時也有不同款式防水型設定適用於室外使用。
- ▶ **AR-0600M** 獲三項國際專利: 專利防殘磁設計 (專利證號: Taiwan M597321 / EP 20168850.4-1005 / China 202010170047.8)
防鎖體掉落專利設計 (專利證號: USA 16/828.910 / Taiwan I679336/ EP 20168852.0-1005 / China 202010227686.3)
鎖體結構強化 (專利證號: USA 16/828.931 / Taiwan I679336 / EP 20168852.4 / China 202010227687.8)

室內型磁力鎖								室外型磁力鎖		
AR-0090M	AR-0180M	AR-0200M	AR-0300M	AR-0600M	AR-0600M-R (埋入式)	AR-1200M	AR-0400WF (正孔)	AR-1500WF (正孔)		
				 AR-0600M-DB (雙門) 		 AR-1200M-DB (雙門) 				
12VDC/24VDC								12VDC/24VDC		
工作電壓	12VDC/24VDC								12VDC/24VDC	
消耗電流	130mA/12VDC 60mA/24VDC	200mA/12VDC 100mA/24VDC	200mA/12VDC 100mA/24VDC	370mA/12VDC 185mA/24VDC	500mA/12VDC 250mA/24VDC	400mA/12VDC 200mA/24VDC	500mA/12VDC 250mA/24VDC	370mA/12VDC 185mA/24VDC	500mA/12VDC 250mA/24VDC	
材質	鎖體外殼: 鋁合金 ; 吸附鐵板: 純鐵 ; 支架: 鋁合金								鎖體外殼: 不鏽鋼 / 吸附鐵板: 純鐵 / 支架: 鋁合金	
拉力(kg)	40	80	110	150	270	250	500	180	600	
使用壽命	超過500,000次								超過500,000次	
溫度	鎖體表面溫度								鎖體表面溫度	
	環境溫度								環境溫度	
濕度	0~95% non-condensing								0~95% non-condensing	
尺寸(mm)	磁力鎖: 37(H) x 70(W) x 25(D) (L Bracket included) 吸附鐵板: 32(H) x 60(W) x 8(D)	磁力鎖: 38(H) x 100(W) x 38(D) 吸附鐵板: 28(H) x 74(W) x 8(D) 支架 (內附): 74(L) x 28(W) x 48(H)	磁力鎖: 28(H) x 160(W) x 20(D) 吸附鐵板: 28(H) x 130(W) x 9(D)	磁力鎖: 39(H) x 166(W) x 21(D) 吸附鐵板: 32(H) x 130(W) x 10(D)	AR-0600M 磁力鎖: 47(H) x 251(W) x 25(D) 吸附鐵板: 38(H) x 185(W) x 12(D) AR-0600M-DB 磁力鎖: 48(H) x 502(W) x 25(D) 吸附鐵板: 38(H) x 185(W) x 12(D)* 2units	磁力鎖: 38(H) x 228(W) x 27(D) 吸附鐵板: 50(H) x 185(W) x 45(D)	AR-1200M 磁力鎖: 74(H) x 266(W) x 40(D) 吸附鐵板: 61(H) x 185(W) x 16(D) AR-1200M-DB 磁力鎖: 74(H) x 532(W) x 40(D) 吸附鐵板: 61(H) x 185(W) x 16(D)* 2units	AR-0400WF 磁力鎖: 35(H) x 164(W) x 27(D) 吸附鐵板: 32(H) x 130(W) x 11(D) AR-0400WS 磁力鎖: 41(H) x 164(W) x 27(D) 吸附鐵板: 32(H) x 130(W) x 10(D)	AR-1500WF 磁力鎖: 63(H) x 203(W) x 40(D) 吸附鐵板: 61(H) x 185(W) x 17(D) AR-1500WS 磁力鎖: 70(H) x 224(W) x 42(D) 吸附鐵板: 61(H) x 185(W) x 16(D)	
	LZ支架	內附 L 支架	—	—	AR-0300MZL (L與Z支架可單獨選購)	AR-0600MZL (L與Z支架可單獨選購)	—	AR-1200MZL (L與Z支架可單獨選購)	AR-0400MZL (L與Z支架可單獨選購)	AR-1500MZL-WF AR-1500MZL-WS
支架	鐵板支架	—	—	—	AR-0600M-MA	—	AR-1200M-MA	—	—	
	U型夾	—	—	—	AR-0300M/0400M-U	AR-0600M-U	—	AR-0300M/0400M-U	—	
電磁鎖淨重(kg)	約0.25kg	約0.75kg	約0.6kg	約0.95kg	AR-0600M: 約1.2kg AR-0600M-DB: 約3.1kg	約1.01kg	AR-1200M: 約3.2kg AR-1200M-DB: 約6.2kg	AR-0400WF: 約0.90kg AR-0400WS: 約1.30kg	AR-1500WF: 約3.10kg AR-1500WS: 約3.50kg	
門位偵測輸出	NO			YES	YES (All type)	YES NO	YES (All type)	—	—	
LED指示器	NO			NO	YES (All type)	YES NO	YES (All type)	—	—	
防塵防水等級	—								IP66	

	LZ 支架						鐵板支架		U型玻璃夾	
	AR-0300MZL	AR-0600MZL	AR-1200MZL	AR-0400MZL	AR-1500MZL-WF	AR-1500MZL-WS	AR-MA-46190	AR-1200M-MA	AR-0300M/0400M-U	AR-0600M-U
尺寸(mm)	L 支架: 43(H)x166(W)x29(D) Z 支架: 43(H)x166(W)x43(D)	L 支架: 50(H)x250(W)x33(D) Z 支架: 50(H)x190(W)x50(D)	L 支架: 75(H)x266(W)x48(D) Z 支架: 72(H)x190(W)x72(D)	L 支架: 43(H)x166(W)x33(D) Z 支架: 43(H)x166(W)x100(D)	L 支架: 69(H)x198(W)x43(D) Z 支架: 66(H)x184(W)x66(D)	L 支架: 72(H)x190(W)x144(D) Z 支架: 78(H)x225(W)x48(D)	46(H)x190(W)x19.5(D)	67.5(H)x190(W)x21(D)	50(H)x110(W)x22(D)	50(H)x210(W)x22(D)